



EL-150

The EL-150 is a fixed window available in a variety of shapes to meet a wide range of applications. This window is used to bring light to places with difficult accessibility.

System Description

- Large missile impact rated
- 3" frame depth
- Water infiltration: 12 psf
- Design load: +80/-80 psf large missile impact rated
- U-value:
 - IGU-0.46
 - 5/32" clear SB60 (#2) + 5/16" Air Spacer + 5/32" clear + 0.075" PVB + 5/32" clear Low E (#6)
 - LG-1.01
 - 3/16" clear + 0.09" PVB + 3/16" clear
- Insulating-laminated glass
 - 1/8" + 5/16" spacer + 1/8" + 0.09" interlayer + 1/4"
 - 5/32" + 5/16" spacer + 5/32" + 0.09" interlayer + 5/32"
- Laminated glass
 - 1/8" + 0.09" interlayer + 1/4"
 - 3/16" + 0.09" interlayer + 3/16"
- Standard Egress Size: 35 5/8" x 64" and 25 5/8" x 88 1/2".

Features

- Flange frame for masonry, fin frame for wood construction or flush frame for concrete openings
- Architectural shapes available
- Minimum radius: 14"
- Saflex PVB, Kuraray PVB, Vanceva Storm and Sentry glass Plus interlayer options.

