

EL-200

The EL-200 is a horizontal sliding window. This product is designed to ensure smooth, easy operation and to allow maximum ventilation. This product can be used for a wide variety of applications.

System Description

- Large missile impact rated
- 3" Frame depth.
- Configurations: XO, OX or XOX. (1/4, 1/2, 1/4, 1/3, 1/3, 1/3)
- Designed for multiple laminated glass options.
- Water infiltration: 12 psf large missile impact rated
- Design load: 80/90 psf large missile impact rated
- Maximum size: 111" x 63" XOX
- U-value:
 - IGU-0.48
 - 1/8" clear SB60 (#2) + 5/16" Air Spacer + 1/8" clear + 0.75" PVB + 1/4" Clear Low E (#6)
 - LG-1.0
 - 1/8" clear + 0.09" PVB + 1/8" clear
- Insulating laminated glass
 - 1/8" + 3/8" spacer + 1/8" + 0.09" interlayer + 1/8"
 - 1/8" + 5/16" spacer + 1/8" + 0.09" interlayer + 1/4"
- Laminated glass
 - 1/8" + 0.09" interlayer + 1/8"
 - 1/8" + 0.09" interlayer + 1/4"
- Egress Size: 72 3/8" X 30 1/8" and 52" X 42 1/8".

Features

- Polyamide rollers with needle bearings
- Spring latch at jamb or sweep lock options
- Flange or fin frame for masonry and wood construction, flush frame for concrete openings
- Saflex PVB, Kuraray PVB, Vanceva Storm and Sentry glass Plus interlayer options.

