

EL-400

The EL-400 is a sliding glass door with a 4 9/16" frame profile. This product meets the most stringent specifications and, with its attractive design and three-track frame, is ideal for a wide range of applications.

System Description

- Large missile impact rated
- 4 9/16" Frame depth
- Configurations: XO, OX, XX, OXO, OXXO, XXXX, OXXXXO
- Water infiltration: 12 psf
- Design load: +80/-80 psf
- Maximum size: 288" X 108"
- U -value:
 - IGU-0.52
 - 3/16" clear SB60 (#2) + 3/8" Air Spacer + 3/16" clear + 0.090" PVB + 3/16" Low E (#6)
 - LG-1.04
 - 3/16" clear + 0.09" PVB + 3/16" clear
- Insulating laminated glass: 3/16" + 3/8" spacer + 3/16" + 0.09" interlayer + 3/16"
- Laminated glass: 3/16" + 0.09 interlayer + 3/16"
- Minimum width for accessibility is 75 5/8 on OX/XO configuration and 81 7/8 on XX configuration

Features

- Adjustable tandem polyamide needle bearing rollers
- Three track and four track frame option
- Saflex PVB, Kuraray PVB, Vanceva Storm and Sentry glass Plus interlayer options
- Pocket configuration available

